

REVIEW ON STATIC & DYNAMIC ANALYSIS OF AEROFOIL BLADE AT DIFFERENT ASPECT OF RESEARCH INVESTIGATION

¹Narendra D. Khairnar, ²Dr. Avinash D. Bagul, ³Satish Gambhir Borase

Research Scholar, Deptt. of Mech. Engg., Gangamai CoE, Nagaon, KBC North Maharashtra University, Jalgaon (India)¹, Associate Professor, Deptt. of Mech. Engg., Gangamai CoE, Nagaon, KBC North Maharashtra University, Jalgaon (India)², Assistant Professor, Deptt. of Mech. Engg., Gangamai CoE, Nagaon, KBC North Maharashtra University, Jalgaon (India)³
narendrakhairnar2020@gmail.com¹, avinashbagul58@gmail.com², satish.17515@gmail.com

ABSTRACT

An optimised designed of air foil blade is required for highest quantity of wind power along with both to increase lift and reduce drag, as a whole research area have to be enhanced to the static & aerodynamic performances. To improve the aerodynamics of blade, aerofoil design is crucial. The efficiency of aerodynamics of the blade is requires to be balanced with the loads on the system. So, several geometric specifications are required to solve problem, not just one. But other factors like Aerofoil combination legacy and different function of blade. The geometrical and operational characteristics like speed ratio of tip, velocity of wind, robustness, blade number and shape of blade are also taken into account. The span of aerofoil blade aerodynamic helps in decrease of noise, control over stall condition during dynamic response, independent properties, along unstable condition with distorted air flow state. Conventional instruments for theoretical work of dynamic methods like stage charts, diagrams of bifurcation along with containers are applied for examine & comprehends, the dynamic response exhibits common aerofoil part. Steady-straight jet with given momentum coefficient, is the least effective technique, while the control performance of a steady-angled jet is superior. Due to the creation of stream wise vortices that in order to energize the boundary layer, which combines maximum velocity fluid along minimum velocity fluid close the wall. Increasing pressure and decreasing downstream flow separation allowed the unsteady-oscillating jet to operate at highest efficiency.

Keywords: *Aerofoil, Wind speed, Blade shapes, Blade number, Static, Dynamic.*

INTRODUCTION

Aerodynamics is the science that studies the behaviour of objects in airflow and the physical laws of the forces produced by airflow. In the early stages, aerofoil configuration of blade is restricted to analytical studies, domain tests, & the wind tunnel tests, that requires significant effort and resources. The choice of blade airfoil shape is the most important part of aerospace and wind turbine design, as the blades are ultimately responsible for converting kinetic energy into mechanical energy. Therefore, relatively low Reynolds numbers of flow are subject of relatively few analytical, numerical, & experimental research. Effective aerofoil blade forms have been the subject of more research directed for large kinetic energy acquire from the wind power. Introducing tools that help designers greater understanding their design complexity and location of blade, that are likely to have lower energy costs. An optimal aerodynamic pattern that can respond to a given type of flow conditions is crucial. Now a days, aerodynamic form optimization is developed into important because mechanical & aeronautical engineering are developing so fast. Aerofoil blade design is truly a multi- objective engineering task.

The aerodynamic performance must be balanced with the system loads generated by different parameters under different working conditions. Aerodynamic blades are often considered thin-walled cantilever beams. This assumption helps simplify structural

modelling. To achieve computation effectiveness, Blade Element Moment Method (BEM) is applied as aerodynamic model.




Fig.-1. Review Structure.

Finite element modelling (FEM) facilitates quantitative studies and provides an understanding of deformation mechanics. The beam model with external aerodynamic forces is provided by the BEM model, i.e. both axial and tangential for every cross section. The vibrating blade is the result of outside forces. Induced Vibration velocities in flap direction along edge direction in every part will influence the computation as well of the aerodynamic force, at entry perspective. Twisting causes a modification in the helix direction; it must take into account. In the last several decades scientist & engineers have been more interested in examining flows surrounding aerofoil and blades of turbine to enhance its functionality [1]. BEM method is extensively used, because to its great efficiency, to predict, the aerodynamicsof wind turbines & their operation in both conditions [2].




Fig.-2. Aerofoil Blade. [31].

The BEMs parameterisation system & parameters rely on the on use 2D static aero- foil aerodynamic coefficients for different angles of attack in continuous flows which are typically derived using 2D Naviers-stokes Number [3], or tests conducted in wind tunnel. It is inherently questionable, If the BEM is accurate for vibration. Unsteady flow over wind turbines has an impact on their efficiency & can result in important aerodynamic phenomenon like dynamic stall delay of an aerofoil blade beyond its static stall point.[4]. There are several vortices that are created in relation to the dynamic stall [5] state, a device & aerodynamic shape that can be controlled to change the wind turbine blades aerofoil dynamic performance. In the optimum process of optimization, parametric method in aerodynamic form is sessional [7]. The gas turbine in power plants depends mainly on rotors. Due to unique working circumstances, several corrosive mechanisms are caused by high temperature of airflow passing through the blades & complex force system acting on them. Blade corrosion process can be short of lifespan when it became active. The literature indicates that, oxidation, hot corrosion, fatigue, creep & erosion damage as well as environmental effects are main causes of failure of blades. [8, 9]. The cracks develop through fatigue-creep phenomenon. Generally, creep damage lower fatigue life span and responsible for component failure. [9, 10]. A thorough fault analysis of blades is required in order to identify problem and raise the urbane system dependability [11, 12]. The power & efficiency of gas turbine have been improved by increasing operating temperatures. Gas turbine is built of

super alloys based on nickel & cobalt, because these materials can bear both high temperatures and high stress [13]. A typical grade of metallic material known as super alloys has special set of mechanical characteristics, including strength at high temperatures & resistance to oxidation in the environment. [14].

LITERATURE REVIEW

M. Nachtane et al. (2020), Technological developments in hydrofoil design Includes hydrodynamic designs & mechanical structural design, which are applied in the horizontal axis. Optimization methods for hydrofoil designs & TCT performance are accessed using numerical model [18].

R. M. Ajjaj et al. (2021), Aeroelastic stability comprises research done on morphing techniques to make sure that they meet certain aeroelastic limitations and that limitations do not reduce the possible advantages of morphing. Research on morphing technologies for enhancing aeroelastic properties and managing loads which included in the field of aeroelastic control [19].

Kolagar A. M. et al. (2017) a gas-powered generator efficiency is greatly impacted by turbine blades. The super alloy use to make blade has a nickel basis & after 65000 hrs. of use the aerofoil blade fails [20].

G. R. Fischer et al. (2013), Using a load deflation tool and computational blade optimization tool. The multi-objective turbine thrust optimization yields three extreme configurations. Generating the geometry, use of the panel code to create the airfoil poles and the fixed-wing element moment code to evaluate the turbine performance. It is possible to fabricate a wing with a feasible multi-layer arrangement, which can increase energy harvesting and reduce steady-state system load. [21].

Hang Meng et al. (2018), analyses bend coupling, also known as aero elasticity, reducing fatigue stress on blades is often accomplished through passive pitch control. This reduces aerodynamic forces by reducing an angle of attack at a rapid increase in load with coupling. BTC effect reduces the fatigue effect, which has an effect blade life and is determined by structure [22].

T.E. Boye et al. (2022) determine an operational with design parameter like that, speed ratio of blade tip, air velocity, blades numbers, blade shape at reduced frequencies of zero. Reduced high frequencies pitch motion improves tip vortex suppression during ascent and slows boundary layer reattachment with very low angle of attack during descent. At high Reynolds, with aerofoil cross section, the influence of high & low frequencies of the blade under a deep dynamic chamber [23].

M. Koklu et al (2017) Traditional methods of controlling flow, flow Such as stable and unsteady vortex jets, continuous blowing & micro blowing generators are contrasted with swept jet actuators. The swept jet actuators are operated in here modes to generate unsteady oscillations and constant angle straight beams to directly compare the results [24].

J. Peirò et al. (2021) Employ the Runge-Kutta-Fehlberg algorithm with event detection to integrate the equations of motion, since the loads supplied by this model are nonlinear and not continuous. motion simulation throughout arranges of Mach number with a model that is very sensitive to even small changes. By analyzing the evaluation of their attractors zones as the Mach Number varies, the mechanism of co-existing attractors appearance and disappearance is clarified. [25].

P.A. Roy et al. (2021) A numerical solution that is accurate, unified, and consistent is developed in consent of dynamic response about metal-matrix composite (MMC) blade and silicon carbide (SiC) fibers are used to strengthen and the titanium along to make MMC blade. Creating a cohesive method to explain the dynamic behaviour of blades is first component with SiC strengthening the blades inherent frequency can be raised by decreasing its weight. Pre-torsion angle determines the natural bending and torsion frequencies. [26].

B. Mohameda et al., states that, the test surface shows that fiber orientation affects the ultimate breaking strength, and fibers-oriented composites materials works better in parallel the direction of tensile strength. Performance of these patches is affected by the element of stress intensity in connection with affected region & fiber orientation. In a way fibers are oriented affects the composite material & how well it repairs the damage [27].

DISCUSSIONS & FUTURE PERSPECTIVE

Large span aerofoil blades suitable for longer endurance, but it also makes less maneuverability & subject to more root bending moments. Small span on the hand, provides for greater maneuverability and agility but at the expense of less endurance. It is necessary to have a Aerofoil blade shape least susceptible for a roughness on the surface. Additionally, blade tip needs to have a gradually thicker because the hub part is subjected to different loads structurally. The strength and camber blades increased with thickness, which enhanced the hydrodynamic properties of the hydrofoil blade. Since the blades experiences high thrust forces, the material selected should have sufficient strength to minimize or avoid blade fouling & stop cavitation-erosion, which reduces maintenance expenses. Strengthening the structure it also requires strong material. Under specified boundary conditions and static applied load, the behaviour of elastic materials is the focus of linear static analysis. In these circumstances, thrust is the applied load acting on the blades [28].

Table-I. Deflection & Stresses in Aluminium Material under static condition. [Table-I-32]

Results	Material (Al)
Stress- a. Von Mises	6.883 N/mm ²
b. Normal	485.337 N/mm ²
Blade Deviation (mm)	6.883
Principal Stress (First)	518.775 N/mm ²
Principal Stress (Second)	206.945 N/mm ²

Table II. Static Analysis results of Composite Material. [Table-II-32]

No. of Layers	Normal Stress in N/mm ²	Von Mises Stress (N/mm ²)	Blade Deviation in (mm)	Shaer Stress N/mm ²
16	79.5111	101.876	0.488923	53.01
12	78.784	101.099	0.4846	52.44
8	77.611	99.276	0.47721	52.146
4	77.555	97.038	0.479367	51.327

It is observed that, as compared to aluminium material, composite material experience maximum deflection, while composite material has minimum amount of stress. Elastic skins such as silicon elastomers, Carbon Kevlar Composites, Rubber sheets, and Elastic matrix composites (EMC) are used in morphing concepts. The aerodynamic shape along skins has a significant influence on the blade's structural properties. Again, majority of flexible skins have nonlinear behaviour, which the aerodynamics elastic model needs to take into consideration. Some of the research works have looked at how flexible morphing skins affects the dynamic performance of blade. There have been notable developments in the near decenniums, in the creation of modern floating platform design concepts and numerical model for simulation of aerofoil blade for its dynamic response. To produce more affordable designs and to acquire a better understanding of their dynamic reaction, additional research and developments work along with a preparatory stage of technological advancements are required. Identify and optimize blade designs with low energy costs.

CONCLUSION

It is evident that the majority of research is computational or numerical, with very few mechanical and tunnel testing. It is observed that, very few flight test conducted. The important is that to minimize weight & cost while maximizing power coefficient, limiting cavitation, resisting severe and fatigue loads, along limiting tip deflections. Structural problems like mass, corrosion resistance, fouling resistance, manufacturing process and coating technologies, among others. Further, the use of Computer-Aided design offers an alternative approach to designing & analysing aerofoil blades. Further, majority of aerodynamic models which are using low fidelity methods. The structural analysis for aeroelastic research is more advanced, using a range of models. The bulk of the work is limited to minimal subsonic velocity. Because of inherent complexity, structural non linearities should be addressed.

REFERENCES

- [1] T. E. Boye, Z T. Xie, (2022), Acronymic of A Pitching Wind Turbine Blade at High Reduced Frequencies, Science Direct Journal of Wind Engineering & Industrial Aerodynamics, Vol. -223, 104935.
- [2] M.O. Hansen, (2015), Aerodynamics of Wind Turbines, Routledge.
- [3] Ghasemian et al. M. Ashrafi, Z. N. Sedaghat, (2017), A Review on Computational Fluid Dynamic Simulation Techniques for Darrieus Vertical Axis Wind Turbines, Energy conversion, M149, pp.87-100.
- [4] Lee & Gerontakos, T. Lee, (2004), Investigation of Flow over an Oscillating Aerofoil, Journal of Fluid Mech. 512, pp - 313-341.
- [5] R-Eguia, I. Errata, I. Fernandez-Gamiz, U. Blanco, J. Zulueta, E. Saenz-Aguirre, (2020), A Parametric Study of Trailing Edge Flap Implementation on Three Different Aerofoils Through an Artificial Neuronal Network, Symmetry, 12-828.
- [6] L. K. Marshall, (2009), Surface Parametrization Method for Aerofoil Optimization & High Lift 2D geometries utilizing the CST Methodology, 47th AIAA Aerospace Sciences Proceedings, The New Horizons Forum & Aerospace exposition, Orlando.
- [7] P. W. Schilke, (1980), GE Poer System, General Electric Company, Report M-715, 1-18.
- [8] Strang, (2000), GE Poer System, General Electric Company, Report M-912, 319-332.
- [9] Kaul A.K., Imariageon J.P., Parameswaran V. R., Wallace W. (1994), Advances in high temperature structural materials & Coatings, National Research council of Canada, Ottawa.
- [10] Wang W. & Xuan F. (2007), Failure Analysis of the Final Stage Blade in Steam Turbine, Journal of Engg Failure Analysis, 14632-41.
- [11] Chang E. & Chou J. C. Microporosity in an Investment- casting turbine Blade of IN713LC superalloy AFS Transaction, 95-749-754.
- [12] Decker R. F., Sims C.T. & Hagel W. C. (1984), The superalloy I, New York, John Wiley & Sons-33-37.
- [13] Bhaumik S. K. Sujata M. (1981) Failure of a low -pressure turbine rotor blade of an aero engine, Journal of Engg. Failure Analysis,13,1202-19.
- [14] Steven R. A., Flewith P.E., (1981) Intermediate Regenerative Haet Treatment for Extending the Creep life of superalloy, IN738, Material Science & Engineering, 50-271-248.
- [15] Barbirinao O., Bilgen R.M., Ajaj M. I. Friswell D. J., Inman D.J. (2011), A review of morphing aircraft, Journal of Intellectual, Master System Structure-22, 823-877, <https://doi.org/10.1177/1045389X11414084>.

- [16] Nachtane M., Tarfaoui A., Moumen E. I. Saifaoui D. (2017), Damage prediction of horizontal axis marine current turbines under hydrodynamic, hydrostatic & Impacts loads, *Composite Structure*, 170-146e157.
- [17] Nachtane M., Tarfaoui A., Moumen E. I. Saifaoui D., Hasoon O. H., Benyahia H. (2018) Evaluation of durability of composite materials applied to renewable marine energy- case of ducted tidal turbine, *energy*, Rep.-4-31e40.
- [18] Nachtane M., Tarfaoui, Goda I., Rouway M., (2020) A review on the technologies, design consideration & numerical models of tidal current turbines, *Renewable energy*-157- 1274e1288.
- [19] Ajaj R. M., Parancheeri M. Reza M., Friswell M.I., Cantwell W. J.,(2021), Recent developments in the aeroelasticity of morphing aircraft, Elsevier , *progress in Aerospace Sciences* 120-100682,
- [20] Kolagar A. M. Tabrizi N., Cheragh Zadeh M., Shahriari, (2017) Failure analysis of gas turbine first stage blade made of nickel- based superalloy, <http://dx.doi.org/10.1016/j.csefa.2017.04.002>.
- [21] Fischer G.R. Kipouros T., Anthony M. S. (2013) Multiobjective optimization of horizontal axis wind turbine structure & energy production using aero foil & blade properties as design variables, *Renewable Energy*-62 -506e515.
- [22] Meng H. Lien F. S. , Glinka G. Geiger P. , (2018) Study on fatigue life of bend-twist coupling wind turbine blade based on anisotropic beam model & stress based fatigue analysis method,
- [23] Ghasemian M. Ashrafi Z.N. Sedaghat A., (2017) A review on Computational Fluid dynamic simulation technique for Darrieus vertical axis wind turbine, *energy conversion & management* 149-87-100.
- [24] Mehti K., Lewis R. O.(2017), comparison of sweeping jet actuators with different flow- control Technique for flow-separation control, *AIAA Journal*, Vol.55 No.-3, 10.2514/1.J055286.
- [25] Roy P.A., Hu Y. Meguid S.A., (2021), Dynamic Behaviour of Pretwisted Meal Matrix Composite Blades, *Science Direct, Elsevier, Composite Structures*-268
- [26] Mohmeda B. Khaoulac A. , Leila B. , (2022), effect of the fibers orientation of the different types of composites plates notched of U-shape repaired by composite patch, <https://doi.org/10.1590/1980-5373-MR-2022-0302>.
- [27] Galvanetto, Peiro J. , Chantharasenawon, C. (2007) Remarks on the nonlinear dynamics of a typical aero foil section in dynamic stall, *The Aeronautical Journal*.
- [28] Barbarino S. Bilgen O., Ajaj R.M. Friswell M.I., Inman D.J. , (2011), A review of morphing aircraft future perspective, *J. International Material system structure*-22-823-877, <http://doi.org/10.1177/1045389X1144084>.
- [29] Tausif M. A., Kim M. H. (2021), CFD Analysis & Shape Optimization Of Air Foil Using Class Shape Transformation & Generic Algorithm, *Applied Science* -11379, <https://doi.org/10.3390/app1109379>.
- [30] Naung S.W., Nakhchi, Rahmani M., (2021), An experimental & Numerical study on the Aerodynamics Performance of vibrating wind turbine blade with frequency-Domain method, DOI: 10.22055/JACM.2021.37406.3011J, *Applied Computer/ Mechanical*, 7(3),737-1750, ISSN:2383-4536.
- [31] Sagar M.V., Venkaiah M., Dr. D. Sunil, (2013), Static & Dynamic analysis of composites propeller of ship using FEA, *International journal of Engineering Research & Technology*, Volume-2 Issue 7.
- [32] anigrah, Devi P. M., (2014) CFD simulations for the selection of an appropriate blade profile for improving energy efficiency in axial flow mine ventilation fans, *Journal of sustainable mining*, E-ISSN 2300-3960-1354-1364.